



SPECIFICATIONS:

- Suitable Rated Current : 30A Max.
- Dielectric Strength for 60 Seconds : AC 1500V Min
- Insertion & Extraction Force : 1kg. Min
- Contact Resistance at 1A DC : 5mΩ Max.
- Insulation Resistance at 500V DC : 100MΩ Min.
- Voltage Drop : 20mV Max.
- Temperature Rise : 50°C Max.
- Type : Water Resistance Type, Crimping Type
- Molded Parts : P.V.C.
- Terminals : Brass, Accept Wire #16-12 AWG

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material	Drawn	GLORYTECH TECHNOLOGY CO., LTD.				
	Check					
Finish	Engr	Title:	A	GTQD-HLD-1822-1903	B	
	Appd					In-Line Fuse Holder
Unless Otherwise Specified Dimensions are mm (inch) Tolerances:		Scale:	1:1	Dwg Size	Sht 1 of 1	Rev
.x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		Model File Name : In-Line Fuse Holder for Blade Type Fuses				
Drawing File Name : GTQD-HLD-1822-1903						
Part Number : 1822 1903 400				Date:	2004/9/24	