



SPECIFICATIONS:

Suitable Rated Current : 80A Max.
 Dielectric Strength for 60 Seconds : AC 3000V Min
 Insertion & Extraction Force : 1kg. Min
 Contact Resistance at 1A DC : 5mΩ Max.
 Insulation Resistance at 500V DC : 100MΩ Min.
 Voltage Drop : 20mV Max.
 Temperature Rise : 50°C Max.
 Wire : UL 1028 ; 6" Each End
 Type : Water Resistant Type
 Molded Parts : P.V.C.
 Terminals : Brass

Part No.	Wire Size
18222903406	6AWG
18222903421	8AWG

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material		GLORYTECH TECHNOLOGY CO., LTD.				
Drawn	Check	Title: In-Line Fuse Holder		A4	GTQD-HLD-1822-2903	B
Finish	Engr					
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		Appd	Scale: 1:1	Dwg Size	Sht 1 of 1	Rev
Model File Name : In-Line Fuse Holder for Max-Blade Type Fuses						
Drawing File Name : GTQD-HLD-1822-2903						
Part Number : 1822 2903 4XX				Date:	2004/9/24	