



Part No.	18240601421	18240602421
Suitable Rated Current	20A Max.	20A Max.
Dielectric Strength for 60 seconds	AC 1000V Min.	AC 1000V Min.
Contact Resistance at 1A DC	5mΩ Max.	5mΩ Max.
Insulation Resistance at 500V DC	100MΩ Min.	100MΩ Min.
Wire	14# AWG / 8" Loop	14# AWG / 8" Loop
Type	Interlock Type	Interlock Type
Molded Parts	Polycarbonate P.C.	Polycarbonate P.C.
Terminals	Brass	Brass
Color	Black	Red

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material	Drawn		<b>GLORYTECH TECHNOLOGY CO., LTD.</b>				
	Check						
Finish	Engr		Title: In-Line Fuse Holder	A	GTQD-HLD-1824-0601 GTQD-HLD-1824-0602	B	
	Appd						
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)			Scale:	1:1	Dwg Size	Sht 1 of 1	Rev
Model File Name : In-Line Fuse Holder for 6.3x32mm Fuses							
Drawing File Name : GTQD-HLD-1824-0601(0602)							
Part Number : 1824 0601(0602) 421					Date:	2004/9/24	