



SPECIFICATIONS :

1. Suitable Rated Current : 30A Max.
 2. Housing and Cover : PC , Black
 3. Seal : Silicone Rubber , Orange
 4. Wire : 10/12/14//16/18 AWG , UL1015
- * Fuse not included

| | |
|---|----------------------|
| Tolerances : Unless Otherwise Specified | |
| Dimension | Critical To Function |
| < 1 | +/- 0.02 |
| 1 ~ 8 | +/- 0.1 |
| 8 ~ 24.995 | +/- 0.15 |
| 25 ~ 99.99 | +/- 0.2 |
| Angles | +/- 1° |

| Rev | EN | Description | Dwg | Ckd | Appd | Date |
|-----|----------|----------------------|-----|------|------|-----------|
| B | 93092401 | Modify the tolerance | Kao | Chyi | Ku | 2004/9/24 |

| | | | | | | | |
|---|-------|--|--|----------|--------------------|--------|-----|
| Material | Drawn | Title: In-Line Fuse Holder | Scale: | Dwg Size | Sht | 1 of 1 | Rev |
| | Check | | | | | | |
| Finish | Engr | Unless Otherwise Specified Dimensions are mm (inch) | .x = 1.0 (.04) .xxx = 0.5 (.02) .xxx = 0.25 (.010) | A4 | GTQD-HLD-1824-1101 | B | |
| | Appd | | | | | | |
| Model File Name : In-Line Fuse Holder for Mini Blade Fuses ; Waterproof | | Drawing File Name : GTQD-HLD-1824-1101 | | | | | |
| Part Number : 1824 1101 4XX | | Date: 2013/12/13 | | | | | |

GLORYTECH TECHNOLOGY CO., LTD.