



Suitable Rated Current	30A Max.
Dielectric Strength For 60 Seconds	AC 1500V Min.
Insertion & Extraction Force	1Kg. Min.
Contact Resistance At 1A DC	5mΩ Max.
Insulation Resistance At 500V DC	100MΩ Min.
Wire	Suitable for Wire #12 ~ #18 AWG
Type	Waterproof Type, Snap-Lock
Molded Parts	PVC
Terminals	Brass, Crimp Terminals

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material	Drawn		GLORYTECH TECHNOLOGY CO., LTD.				
	Check						
Finish	Engr		Title: In-Line Fuse Holder	A	GTQD-HLD-1827-0602	B	
	Appd						
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)			Scale:	1:1	Dwg Size	Sht 1 of 1	Rev
Model File Name : In-Line Fuse Holder for 6.3x32mm Fuses							
Drawing File Name : GTQD-HLD-1827-0602							
Part Number : 1827 0602 421					Date:	2004/9/24	