



SPECIFICATIONS :

Suitable Rated Current : 30A Max.

Dielectric Strength for 60 seconds : AC1500V Min.

Insertion & Extraction Force : 1Kg. Min.

Contact Resistance at 1A DC : 5mΩ Max.

Insulation Resistance at 500V DC : 100MΩ Min.

Voltage Drop : 20mV Max.

Temperature Rise : 50°C

Molded Parts : Nylon

Wire Length : UL1015, Red, 8" Loop

Terminals : Brass

Interlock Type For Multiple Mounting

Order Information :

Part No.	Wire Size(AWG)
1827 1101 412	12
1827 1101 414	14
1827 1101 416	16
1827 1101 418	18

Option : Wire Length

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material	Drawn	GLORYTECH TECHNOLOGY CO., LTD.			
	Check				
Finish	Engr	Title:			
	Appd	In-Line Fuse Holder		A4	GTQD-HLD-1827-1101
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)				B	
		Scale:	1:1	Dwg Size	Sht 1 of 1
Model File Name : Fuse Holder for Mini / LP Blade Type Fuses					
Drawing File Name : GTQD-HLD-1827-1101					
Part Number : 1827 1101 4**				Date:	2012/5/16