



Cover(P.P.)



Housing



Contact



Wire

SPECIFICATIONS :

Suitable Rated Current : 30A Max.
 Dielectric Strength for 60 seconds : AC1500V Min.
 Insertion & Extraction Force : 1Kg. Min.
 Contact Resistance at 1A DC : 5mΩ Max.
 Insulation Resistance at 500V DC : 100MΩ Min.
 Voltage Drop : 20mV Max.
 Temperature Rise : 50°C
 Molded Parts : Nylon with Glass Fiber
 Wire Length : ULL1015, Red, 5" Each End
 Contact : Brass ,Junior Power Timer
 Interlock Type For Multiple Mounting
 IP Rating : 63

Order Information :

Part No.	Wire Size(AWG)
1827 1102 412	12
1827 1102 414	14
1827 1102 416	16
1827 1102 418	18

Option : Wire Length

Tolerances : Unless Otherwise Specified			
Dimension	Critical To Function	General	
< 1	+/-0.02	+/-0.03	
1 ~ 8	+/-0.1	+/-0.2	
8 ~ 24.995	+/-0.15	+/-0.25	
25 ~ 99.99	+/-0.2	+/-0.3	
Angles	+/-1°	+/-5°	
Rev	EN	Description	Dwg Ckd Appd Date
B	93092401	Modify the tolerance	Kao Chyi Ku 2004/9/24

Material		Drawn	Title:		
Check		Engr	In-Line Fuse Holder		
Finish		Appd	A4 GTQD-HLD-1827-1102		
Unless Otherwise Specified Dimensions are mm (inch)					
Tolerances:					
.x = 1.0 (.04)					
.xx = 0.5 (.02)					
.xxx = 0.25 (.010)					
Scale:			1:1	Dwg Size	Sht 1 of 1
Model File Name : Fuse Holder for Mini Blade Type Fuses					
Drawing File Name : GTQD-HLD-1827-1102					
Part Number : 1827 1102 4xx			Date:	2016/8/9	
Rev					

GLORYTECH TECHNOLOGY CO., LTD.