



## SPECIFICATIONS :

Suitable Rated Current : 30A Max.  
 Dielectric Strength for 60 seconds : AC1500V Min.  
 Insertion & Extraction Force : 1Kg. Min.  
 Contact Resistance at 1A DC : 5mΩ Max.  
 Insulation Resistance at 500V DC : 100MΩ Min.  
 Voltage Drop : 20mV Max.  
 Temperature Rise : 50°C  
 Molded Parts : Nylon with Glass Fiber  
 Wire Length : ULL1015, Red, 5" Each End  
 Contact : Brass ,Junior Power Timer  
 Interlock Type For Multiple Mounting  
 IP Rating : 67

## Order Information :

Part No.	Wire Size(AWG)
1827 1103 412	12
1827 1103 414	14
1827 1103 416	16
1827 1103 418	18

Option : Wire Length

## GLORYTECH TECHNOLOGY CO., LTD.

Material	Drawn
	Check

**Title:**  
In-Line Fuse Holder

**A4 GTQD-HLD-1827-1103**

**B**

Unless Otherwise Specified  
 Dimensions are mm (inch)  
 Tolerances:  
 .x = 1.0 (.04)  
 .xx = 0.5 (.02)  
 .xxx = 0.25 (.010)

**Title:**

**A4 GTQD-HLD-1827-1103**

**B**

Tolerances : Unless Otherwise Specified			
Dimension	Critical To Function	General	
< 1	+/- 0.02	+/- 0.03	
1 ~ 8	+/- 0.1	+/- 0.2	
8 ~ 24.995	+/- 0.15	+/- 0.25	
25 ~ 99.99	+/- 0.2	+/- 0.3	
Angles	+/- 1°	+/- 5°	

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Model File Name : Fuse Holder for Mini Blade Type Fuses ; Waterproof		Date:	2016/8/9
Drawing File Name : GTQD-HLD-1827-1103			
Part Number : 1827 1103 4xx			