



**SPECIFICATIONS :**

Suitable Rated Current : 20A Max.  
 Dielectric Strength for 60 seconds : AC1500V Min.  
 Insertion & Extraction Force : 1Kg. Min.  
 Contact Resistance at 1A DC : 5mΩ Max.  
 Insulation Resistance at 500V DC : 100MΩ Min.  
 Voltage Drop : 20mV Max.  
 Temperature Rise : 50°C  
 Molded Parts : Nylon with Glass Fiber  
 Wire Length : UL1015

Center : 5inch  
 Side : 6inch

Contact : Brass ,Junior Power Timer  
 Interlock Type For Multiple Mounting  
 IP Rating : 67

**Order Information :**

Part No.	Wire Size(AWG)	
	Center	Side
1827 1402 412	12	14
1827 1402 414	14	16

Option : Wire Length

**GLORYTECH TECHNOLOGY CO., LTD.**

Material	Drawn	Title:
	Check	
Finish	Engr	<b>In-Line Fuse Holder</b>
	Appd	
Unless Otherwise Specified Dimensions are mm (inch)		<b>A4</b>
Tolerances:		<b>GTQD-HLD-1827-1402</b>
.x = 1.0 (.04)		<b>B</b>
.xx = 0.5 (.02)		
.xxx = 0.25 (.010)		

Tolerances : Unless Otherwise Specified

Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Model File Name : Fuse Holder for Micro 3 Fuses ; Waterproof		Scale:	1:1	Dwg Size	Sht	1	of	1	Rev
Drawing File Name : GTQD-HLD-1827-1402									
Part Number : 1827 1402 4xx		Date:	2017/1/13						