



SPECIFICATIONS :

- Suitable Rated Current : 20A Max.
- Dielectric Strength for 60 seconds : AC1500V Min.
- Insertion & Extraction Force : 1Kg. Min.
- Contact Resistance at 1A DC : 5mΩ Max.
- Insulation Resistance at 500V DC : 100MΩ Min.
- Voltage Drop : 20mV Max.
- Temperature Rise : 50°C
- Molded Parts : Nylon
- Terminals : Brass
- Supply Standard UL Wire-AWG/Length:14#AWG/8"Loop

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material		Drawn	GLORYTECH TECHNOLOGY CO., LTD.			
Finish		Check	Title:		A	B
		Engr	In-Line Fuse Holder		GTQD-HLD-1827-1903	
		Appd	Scale:	1:1	Dwg Size	Sht 1 of 1
		Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)				Rev
Model File Name : In-Line Fuse Holder for Blade Type Fuses						
Drawing File Name : GTQD-HLD-1827-1903						
Part Number : 1827 1903 421					Date:	2004/9/24