



**SPECIFICATIONS :**

Suitable Rated Current : 20A Max.

Dielectric Strength for 60 seconds : AC1500V Min.

Insertion & Extraction Force : 1Kg. Min.

Contact Resistance at 1A DC : 5mΩ Max.

Insulation Resistance at 500V DC : 100MΩ Min.

Molded Parts : Nylon

Terminals : Brass

Supply Standard UL Wire-AWG/Length:14#AWG/8"Loop

Part Number	18271904421	18271905421
Color	Black	White

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material	Drawn		<b>GLORYTECH TECHNOLOGY CO., LTD.</b>				
	Check						
Finish	Engr		Title: In-Line Fuse Holder	A	GTQD-HLD-1827-1904 GTQD-HLD-1827-1905	B	
	Appd						
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)			Scale:	1:1	Dwg Size	Sht 1 of 1	Rev
Model File Name : In-Line Fuse Holder for Blade Type Fuses							
Drawing File Name : GTQD-HLD-1827-1904(1905)							
Part Number : 1827 1904(1905) 421				Date:	2004/9/24		