



SPECIFICATIONS :

- Suitable Rated Current : MAX. installation Rating up to 20A.
- Dielectric Strength for 60 seconds : AC1500V Min.
- Insertion & Extraction Force : 1Kg. Min.
- Contact Resistance at 1A DC : 5mΩ Max.
- Insulation Resistance at 500V DC : 100MΩ Min.
- Voltage Drop : 20mV Max.
- Temperature Rise : 50°C Max.
- Molded Parts : Nylon UL 94V-0
- Terminals : Brass with Tin Plated
- Suitable Wire Gauge : #16 AWG UL 1015

| | | | |
|---|----------------------|----------------------|-----------------------|
| Tolerances : Unless Otherwise Specified | | | |
| Dimension | Critical To Function | General | |
| < 1 | +/-0.02 | +/-0.03 | |
| 1 ~ 8 | +/-0.1 | +/-0.2 | |
| 8 ~ 24.995 | +/-0.15 | +/-0.25 | |
| 25 ~ 99.99 | +/-0.2 | +/-0.3 | |
| Angles | +/-1° | +/-5° | |
| Rev | EN | Description | Dwg Ckd Appd Date |
| B | 93092401 | Modify the tolerance | Kao Chyi Ku 2004/9/24 |

| | | | | | |
|--|--|-------|--|--|--|
| Material | | Drawn | GLORYTECH TECHNOLOGY CO., LTD. | | |
| Check | | | | | |
| Engr | | | | | |
| Finish | | Appd | Title: Fuse Tap | | |
| Unless Otherwise Specified Dimensions are mm (inch) | | | A4 GTQD-HLD-1829-1110-400 B | | |
| Tolerances: | | | Dwg Size Sht 1 of 1 Rev | | |
| .x = 1.0 (.04) | | | 2:1 | | |
| .xx = 0.5 (.02) | | | Date: 2015/5/6 | | |
| .xxx = 0.25 (.010) | | | Model File Name : Fuse Tap for Low Profile Mini Blade Fuse | | |
| Drawing File Name : GTQD-HLD-1829-1110-400 | | | Part Number : 1829 1110 400 | | |