



SPECIFICATIONS :

Suitable Rated Current : MAX. installation Rating up to 20A.
 Dielectric Strength for 60 seconds : AC1500V Min.
 Insertion & Extraction Force : 1Kg. Min.
 Contact Resistance at 1A DC : 5mΩ Max.
 Insulation Resistance at 500V DC : 100MΩ Min.
 Voltage Drop : 20mV Max.
 Temperature Rise : 50°C Max.
 Molded Parts : Nylon UL 94V-0
 Terminals : Brass with Tin Plated
 Suitable Wire Gauge : #16 AWG UL 1015

Tolerances : Unless Otherwise Specified			
Dimension	Critical To Function	General	
< 1	+/-0.02	+/-0.03	
1 ~ 8	+/-0.1	+/-0.2	
8 ~ 24.995	+/-0.15	+/-0.25	
25 ~ 99.99	+/-0.2	+/-0.3	
Angles	+/-1°	+/-5°	
Rev	EN	Description	Dwg Ckd Appd Date
B	93092401	Modify the tolerance	Kao Chyi Ku 2004/9/24

Material		Material		Material	
Drawn	Check	Engr	Appd	Scale:	2:1
Finish		Title: Fuse Tap		Dwg Size	A4
Unless Otherwise Specified		Dimensions are mm (inch)		Sht	1 of 1
Tolerances:		.x = 1.0 (.04)		Rev	B
.xx = 0.5 (.02)		.xxx = 0.25 (.010)		Model File Name : Fuse Tap for Low Profile Mini Blade Fuse	
Drawing File Name : GTQD-HLD-1829-1110-401		Date:		2015/5/6	
Part Number : 1829 1110 401					

GLORYTECH TECHNOLOGY CO., LTD.