



SPECIFICATIONS :

- Suitable Rated Current : Maximum Installation Rating
- Existing Circuit : 30A
- Add-on Circuit : 20A
- Dielectric Strength for 60 seconds : AC1500V Min.
- Insertion & Extraction Force : 1Kg. Min.
- Contact Resistance at 1A DC : 5mΩ Max.
- Insulation Resistance at 500V DC : 100MΩ Min.
- Voltage Drop : 20mV Max.
- Temperature Rise : 50°C Max.
- Molded Parts : Nylon with glassfiber(UL 94V-0), Black
- Terminals : Brass with Tin Plated
- Wire : #16 AWG UL 1015 Red Wire
- **Other color option is available for "Molded Parts" and "Wire"

Tolerances : Unless Otherwise Specified	
Dimension	Critical To Function
< 1	+/-0.02
1 ~ 8	+/-0.1
8 ~ 24.995	+/-0.15
25 ~ 99.99	+/-0.2
Angles	+/-1°
Rev	EN
93092401	Modify the tolerance
	Kao
	Chyi
	Ku
	2004/9/24

Material	Drawn	GLORYTECH TECHNOLOGY CO., LTD. Title: 3 Circuits LP Tap			
	Check				
Finish	Engr	A4	GTQD-HLD-1829-1121-401	B	
	Appd				
Unless Otherwise Specified Dimensions are mm (inch)		Scale: 1:1			
Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		Dwg Size	Sht	1 of 1	Rev
Model File Name : 3 Circuit LP Tap ; #16AWG		Date: 2017/9/29			
Drawing File Name : GTQD-HLD-1829-1121-401		Date: 2017/9/29			
Part Number : 1829 1121 401		Date: 2017/9/29			