



SPECIFICATIONS :

- Suitable Rated Current : Maximum Installation Rating
- Existing Circuit : 20A
- Add-on Circuit : 15A
- Dielectric Strength for 60 seconds : AC1500V Min.
- Insertion & Extraction Force : 1Kg. Min.
- Contact Resistance at 1A DC : 5mΩ Max.
- Insulation Resistance at 500V DC : 100MΩ Min.
- Voltage Drop : 20mV Max.
- Temperature Rise : 50°C Max.
- Molded Parts : Nylon with glassfiber UL 94V-0, Black
- Terminals : Brass with Tin Plated
- Wire : #16 AWG UL 1015 Red Wire, End With Insulated Crimp-Type coupler Blue Butt Connector
- **Other color option is available for "Molded Parts" and "Wire"

Tolerances : Unless Otherwise Specified		Critical To Function		General		
Dimension	< 1	+/- 0.02	+/- 0.03			
	1 ~ 8	+/- 0.1	+/- 0.2			
	8 ~ 24.995	+/- 0.15	+/- 0.25			
	25 ~ 99.99	+/- 0.2	+/- 0.3			
Angles		+/- 1°	+/- 5°			
Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material		Drawn	Title:		
Check		Engr	Micro 3 Tap		
Appd			A4	GTQD-HLD-1829-1402-400	B
Unless Otherwise Specified Dimensions are mm (inch)			Tolerances:		
.x = 1.0 (.04)			Scale:		
.xx = 0.5 (.02)			1:1		
.xxx = 0.25 (.010)			Dwg Size	Sht	of
Model File Name : Fuse Tap for Micro 3 Fuse ; #16 AWG Wire			1	1	1
Drawing File Name : GTQD-HLD-1829-1402-400			Date:	2017/1/13	
Part Number : 1829 1402 400					

GLORYTECH TECHNOLOGY CO., LTD.