



6.3mm Female Terminal with Plastic Case

SPECIFICATIONS :

- Suitable Rated Current : Maximum Installation Rating
- Existing Circuit : 30A
- Add-on Circuit : 20A
- Dielectric Strength for 60 seconds : AC1500V Min.
- Insertion & Extraction Force : 1Kg. Min.
- Contact Resistance at 1A DC : 5mΩ Max.
- Insulation Resistance at 500V DC : 100MΩ Min.
- Voltage Drop : 20mV Max.
- Temperature Rise : 50°C Max.
- Molded Parts : Nylon PA66 UL 94V-0, Black
- Terminals : Brass with Tin Plated
- Wire : #16 AWG UL 1015 Red Wire
- **Other color option is available for "Molded Parts" and "Wire"

Tolerances : Unless Otherwise Specified	
Dimension	Critical To Function
< 1	+/- 0.02
1 ~ 8	+/- 0.1
8 ~ 24.995	+/- 0.15
25 ~ 99.99	+/- 0.2
Angles	+/- 1°
Rev	EN
93092401	Modify the tolerance
	Dwng Kao
	Ckd Chyi
	Appd Ku
	Date 2004/9/24

Material	Drawn	<p>GLORYTECH TECHNOLOGY CO., LTD.</p> <p>Title: Blade Fuse Tap (Left Side Insert Fuse)</p> <p>A4 GTQD-HLD-1829-1915-401 B</p>			
	Check				
Finish	Engr	<p>Unless Otherwise Specified Dimensions are mm (inch)</p> <p>Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)</p>	Dwg Size	Sht of	Rev
	Appd				
Model File Name : Blade Fuse Tap ; #16AWG ; Left Side Insert		Scale: 1:1	Dwg Size	Sht 1	of 1
Drawing File Name : GTQD-HLD-1829-1915-401		Date: 2015/7/17			
Part Number : 1829 1915 401		Date: 2015/7/17			