



SPECIFICATIONS :

- Suitable Rated Current : Maximum Installation Rating
- Existing Circuit : 30A
- Add-on Circuit : 20A
- Dielectric Strength for 60 seconds : AC1500V Min.
- Insertion & Extraction Force : 1Kg. Min.
- Contact Resistance at 1A DC : 5mΩ Max.
- Insulation Resistance at 500V DC : 100MΩ Min.
- Voltage Drop : 20mV Max.
- Temperature Rise : 50°C Max.
- Molded Parts : Nylon PA66 UL 94V-0, Red
- Terminals : Brass with Tin Plated
- Wire : #16 AWG UL 1015 Red Wire
- **Other color option is available for "Molded Parts" and "Wire"

Tolerances : Unless Otherwise Specified	
Dimension	Critical To Function
< 1	+/-0.02
1 ~ 8	+/-0.1
8 ~ 24.995	+/-0.15
25 ~ 99.99	+/-0.2
Angles	+/- 1°
Rev	EN
93092401	Modify the tolerance
	Kao
	Chyi
	Ku
	2004/9/24

Material	Drawn	Material	Title:	A4	GTQD-HLD-1829-1916-401	B
	Check					
Finish	Engr	Unless Otherwise Specified	(Right Side Insert Fuse)	Dwg Size	Sht	of
	Appd					
Tolerances:		Scale:	1:1	Dwg Size	Sht	of
.x = 1.0 (.04)						
.xx = 0.5 (.02)						
.xxx = 0.25 (.010)		Model File Name : Blade Fuse Tap ; #16AWG ; Right Side Insert		Date:		2015/7/17
Drawing File Name : GTQD-HLD-1829-1916-401		Part Number : 1829 1916 401				

GLORYTECH TECHNOLOGY CO., LTD.