



SPECIFICATIONS :

Suitable Rated Current : Maximum Installation Rating

- Existing Circuit : 30A

- Add-on Circuit : 25A

Dielectric Strength for 60 seconds : AC1500V Min.

Insertion & Extraction Force : 1Kg. Min.

Contact Resistance at 1A DC : 5mΩ Max.

Insulation Resistance at 500V DC : 100MΩ Min.

Voltage Drop : 20mV Max.

Temperature Rise : 50°C Max.

Molded Parts : Nylon PA66 UL 94V-0, Black

Terminals : Brass with Tin Plated

Wire : #14 AWG UL 1015 Red Wire

**Other color option is available for "Molded Parts" and "Wire"

6.3mm Female Terminal
with Plastic Case

Tolerances : Unless Otherwise Specified	
Dimension	Critical To Function
< 1	+/-0.02
1 ~ 8	+/-0.1
8 ~ 24.995	+/-0.15
25 ~ 99.99	+/-0.2
Angles	+/-1°
Rev	EN
93092401	Modify the tolerance
	Dwg Kao
	Ckd Chyi
	Appd Ku
	Date 2004/9/24

Material	Drawn	GLORYTECH TECHNOLOGY CO., LTD. Title: Blade Fuse Tap (Left Side Insert Fuse)					
	Check						
Finish	Engr	A4	GTQD-HLD-1829-1917-401	B			
	Appd						
Unless Otherwise Specified Dimensions are mm (inch)		Dwg Size	Sht	1	of	1	Rev
Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)							
Scale: 1:1		Date:	2015/7/17				
Model File Name : Blade Fuse Tap ; #14AWG ; Left Side Insert		Drawing File Name : GTQD-HLD-1829-1917-401					
Part Number : 1829 1917 401		Date: 2015/7/17					