



SPECIFICATIONS :

- Suitable Rated Current : Maximum Installation Rating
- Existing Circuit : 30A
- Add-on Circuit : 25A
- Dielectric Strength for 60 seconds : AC1500V Min.
- Insertion & Extraction Force : 1Kg. Min.
- Contact Resistance at 1A DC : 5mΩ Max.
- Insulation Resistance at 500V DC : 100MΩ Min.
- Voltage Drop : 20mV Max.
- Temperature Rise : 50°C Max.
- Molded Parts : Nylon PA66 UL 94V-0, Red
- Terminals : Brass with Tin Plated
- Wire : #14 AWG UL 1015 Red Wire, End With Insulated Crimp-Type coupler Blue Butt Connector.
- **Other color option is available for "Molded Parts" and "Wire"

Tolerances : Unless Otherwise Specified	
Dimension	Critical To Function
< 1	+/-0.02
1 ~ 8	+/-0.1
8 ~ 24.995	+/-0.15
25 ~ 99.99	+/-0.2
Angles	+/-1°
Rev	EN
93092401	Modify the tolerance
	Dwg Kao
	Ckd Chyi
	Appd Ku
	Date 2004/9/24

Material		Drawn		Check	
Finish		Engr		Appd	
Unless Otherwise Specified Dimensions are mm (inch)		Tolerances:		.x = 1.0 (.04)	
				.xx = 0.5 (.02)	
				.xxx = 0.25 (.010)	
Title:		Scale:		Dwg Size	
Blade Fuse Tap		1:1		Sht 1 of 1	
(Right Side Insert Fuse)		A4		GTQD-HLD-1829-1918-400	
Model File Name : Blade Fuse Tap ; #14AWG ; Right Side Insert		Date:		2015/7/17	
Drawing File Name : GTQD-HLD-1829-1918-400		Date:		2015/7/17	
Part Number : 1829 1918 400		Date:		2015/7/17	

GLORYTECH TECHNOLOGY CO., LTD.