



SPECIFICATIONS :

- Suitable Rated Current : Maximum Installation Rating
- Existing Circuit : 30A
- Add-on Circuit : 15A
- Dielectric Strength for 60 seconds : AC1500V Min.
- Insertion & Extraction Force : 1Kg. Min.
- Contact Resistance at 1A DC : 5mΩ Max.
- Insulation Resistance at 500V DC : 100MΩ Min.
- Voltage Drop : 20mV Max.
- Temperature Rise : 50°C Max.
- Molded Parts : Nylon PA66 UL 94V-0, Black
- Terminals : Brass with Tin Plated
- Wire : #18 AWG UL 1015 Red Wire, End With Insulated Crimp-Type coupler Blue Butt Connector.
- **Other color option is available for "Molded Parts" and "Wire"

Tolerances : Unless Otherwise Specified	
Dimension	Critical To Function
< 1	+/-0.02
1 ~ 8	+/- 0.1
8 ~ 24.995	+/- 0.15
25 ~ 99.99	+/- 0.2
Angles	+/- .1°
Rev	EN
93092401	Modify the tolerance
	Dwng Kao
	Ckd Chyi
	Appd Ku
	Date 2004/9/24

GLORYTECH TECHNOLOGY CO., LTD.	
Material	Drawn Check
Finish	Engr Appd
Unless Otherwise Specified Dimensions are mm (inch)	
Tolerances:	
.x = 1.0 (.04)	
.xx = 0.5 (.02)	
.xxx = 0.25 (.010)	
Title: Blade Fuse Tap	
(Left Side Insert Fuse)	
A4	GTQD-HLD-1829-1919-400
Scale: 1:1	Dwg Size
	Sht 1 of 1
	Rev
Model File Name : Blade Fuse Tap ; #18AWG ; Left Side Insert	
Drawing File Name : GTQD-HLD-1829-1919-400	
Part Number : 1829 1919 400	Date: 2015/7/17