



**SPECIFICATIONS :**

- Suitable Rated Current : Maximum Installation Rating
- Existing Circuit : 30A
- Add-on Circuit : 15A
- Dielectric Strength for 60 seconds : AC1500V Min.
- Insertion & Extraction Force : 1Kg. Min.
- Contact Resistance at 1A DC : 5mΩ Max.
- Insulation Resistance at 500V DC : 100MΩ Min.
- Voltage Drop : 20mV Max.
- Temperature Rise : 50°C Max.
- Molded Parts : Nylon PA66 UL 94V-0, Black
- Terminals : Brass with Tin Plated
- Wire : #18 AWG UL 1015 Red Wire
- \*\*Other color option is available for "Molded Parts" and "Wire"

Tolerances : Unless Otherwise Specified	
Dimension	Critical To Function
< 1	+/-0.02
1 ~ 8	+/-0.1
8 ~ 24.995	+/-0.15
25 ~ 99.99	+/-0.2
Angles	+/-1°
Rev	EN
93092401	Modify the tolerance
	Dwng Kao
	Ckd Chyi
	Appd Ku
	Date 2004/9/24

Material		Drawn		Title:	
Check		Engr		Blade Fuse Tap	
Appd				(Left Side Insert Fuse)	
Finish		Appd		A4	
Unless Otherwise Specified				GTQD-HLD-1829-1919-401	
Dimensions are mm (inch)				B	
Tolerances:					
.x = 1.0 (.04)					
.xx = 0.5 (.02)					
.xxx = 0.25 (.010)					
Scale:		1:1		Dwg Size	
Model File Name : Blade Fuse Tap ; #18AWG ; Left Side Insert				Sht 1 of 1	
Drawing File Name : GTQD-HLD-1829-1919-401				Rev	
Part Number : 1829 1919 401				Date: 2015/7/17	

**GLORYTECH TECHNOLOGY CO., LTD.**