



SPECIFICATIONS :

- Suitable Rated Current : Maximum Installation Rating
- Existing Circuit : 30A
- Add-on Circuit : 15A
- Dielectric Strength for 60 seconds : AC1500V Min.
- Insertion & Extraction Force : 1Kg. Min.
- Contact Resistance at 1A DC : 5mΩ Max.
- Insulation Resistance at 500V DC : 100MΩ Min.
- Voltage Drop : 20mV Max.
- Temperature Rise : 50°C Max.
- Molded Parts : Nylon PA66 UL 94V-0, Red
- Terminals : Brass with Tin Plated
- Wire : #18 AWG UL 1015 Red Wire
- **Other color option is available for "Molded Parts" and "Wire"

Tolerances : Unless Otherwise Specified			
Dimension	Critical To Function	General	
< 1	+/-0.02	+/-0.03	
1 ~ 8	+/-0.1	+/-0.2	
8 ~ 24.995	+/-0.15	+/-0.25	
25 ~ 99.99	+/-0.2	+/-0.3	
Angles	+/-1°	+/-5°	
Rev	EN	Description	Dwg Ckd Appd Date
B	93092401	Modify the tolerance	Kao Chyi Ku 2004/9/24

Material	Drawn	Title:	Dwg	Sht	of	Rev
	Check					
Finish	Engr	Tolerances:	Scale:	Dwg	Sht	of
	Appd					
Dimensions are mm (inch)		(Right Side Insert Fuse)				
.x = 1.0 (.04)						
.xx = 0.5 (.02)						
.xxx = 0.25 (.010)						
Model File Name : Blade Fuse Tap ; #18AWG ; Right Side Insert						
Drawing File Name : GTQD-HLD-1829-1920-401						
Part Number : 1829 1920 401				Date: 2015/7/17		

GLORYTECH TECHNOLOGY CO., LTD.