



SPECIFICATIONS:

Rating : 60A Max. 12/24/32VDC
 Insulation Resistance : DC 500V 100M ohm Min.
 Dielectric Strength : AC 1000V 1 minute
 Operation Temperature : -25°C ~ +85°C

Fuse Rating	Wire AWG
20A	12AWG
30A	10AWG
40A	8AWG
50A	8AWG
60A	6AWG

Material

Frame : Nylon 66FR7025, Black
 Terminal : Copper
 Nut : Nickel Plated Metal
 Screw : M5*0.8 ; L=5.8mm

GLORYTECH TECHNOLOGY CO., LTD.

Material	Drawn	Title:	A4	GTQD-HLD-1837-2901	B
	Check				
Finish	Engr	Fuse Holder			
	Appd				

Unless Otherwise Specified
 Dimensions are mm (inch)

Tolerances:
 .x = 1.0 (.04)
 .xx = 0.5 (.02)
 .xxx = 0.25 (.010)

Scale:	Dwg Size	Sht	1	of	1	Rev

Model File Name : Fuse Holder for Max.Blade Fuses

Drawing File Name : GTQD-HLD-1837-2901

Part Number : 1837 2901 000

Date: 2018/1/15

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/-0.02	+/-0.03
1 ~ 8	+/-0.1	+/-0.2
8 ~ 24.995	+/-0.15	+/-0.25
25 ~ 99.99	+/-0.2	+/-0.3
Angles	+/-1°	+/-5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24