

SPECIFICATIONS:

- -Pulls and installs both glass type fuse and blade type fuse.
- -Convenient and easily either in or out of the fuse.
- -A must for all car owners.
- -For 3AG Glass Fuse & Blade Type Fuse

Т	Tolerances: Unless Otherwise Specified									
Dii	m ensio	n	Critical To Function					General		
< 1			+ /- 0 . 0 2					+ /-0 .0 3		
1 ~ 8			+ /- 0 .1					+/-0.2		
8 ~	24.99	5	+ /- 0 .1 5					+/-0.25		
2 5	~ 99.99	9	+ /- 0 .2				+/-0.3			
A	ngles		+ /- 1 °			+ /- 5 °		-/- 5°		
Rev	EN		Description	Dwg	Ckd	Appd		Date		
В	93092401	N.	lodify the tolerance	Kao	Chyi	Ku		2004/9/24		
			_							

⅃	Material	Drawn		GLORYTECH TECHNOLOGY CO., LTD.								
	Material	Check										
1	Einich	Finish		Title:								
7	FIIIISII	Appd		Dual T	ype Fuse Puller							
7	Unless Otherwise Specified			1		A	GTQ	в				
H	Dimensions ar	e mm (in	nch)									
┙	Tolerances:											
1	.x = 1.0 (.04)											
╡	.xx = 0.5 (.02) .xxx = 0.25 (.010)		Scale:	1:1	Dwg	Sht	1	of	1	Rev		
-			Scale. 1.1	Size	SIIL		Oi	<u>'</u>	Kev			
┨	Model File Name : Dual Type Fuse Puller											
4	Drawing File Name : GTQD-PUL-6802-0001											
Part Number : 6802 0001 023 Date:								2004/9/24				