



FUNCTIONAL SPECIFICATION :

1. APPLICABLE FOR MEDIUM AND MINI BLADE FUSE.
2. MAXIMUM VOLTAGE OF THE CIRCUIT IN WHICH THE TESTER CAN BE USE IS 14 VOLT.
3. MAXIMUM SHEFT TIME TESTERS IS 2YEARS, AT 20 °C AMBIENT TEMPERATURE.
4. NUMBER OF TESTCYCLES OF 1 SECOND > 2000
5. TWO LED LIGHTS FOR LIGHT UP FUSE WHERE WANT TO CHECK TO CHECK WHEN REPLACE FUSE IN DARKER ENVIROMENT.

PULLER PART :

1. PULLER CAN BE USED TO EXTRACT MEDIUM AND MINI BLADE FUSE.
2. MINIMUM NUMBER OF EXTRACTIONS IS 250.

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material		Drawn	GLORYTECH TECHNOLOGY CO., LTD.			
Finish		Check	Title:		A	B
		Engr	Fuse Lighting tester and Puller		GTQD-PUL-6810-0001	
		Appd	Scale: 2:3		Dwg Size	Rev
		Unless Otherwise Specified Dimensions are mm (inch)		Sht 1 of 1		
		Tolerances:		Date: 2008/10/9		
		.x = 1.0 (.04)				
		.xx = 0.5 (.02)				
		.xxx = 0.25 (.010)				
Model File Name : Fuse Lighting tester and Puller						
Drawing File Name :GTQD-PUL-6810-0001						
Part Number :6810 0001 023					Date: 2008/10/9	