



**SPECIFICATIONS:**

- For High Performance And High Power Audio System, Also Use For Lift Trucks And Other Battery Operated System.
- Body Material : Polycarbonate
- Terminal : Brass/Copper
- Gold Plating

\*Notes : Unless Otherwise Specified

**Electrical Characteristics:**

% of Ampere Rating	Ampere Rating	Opening Time
110%	100 ~ 250 Amp	> 4 Hour
150%	100 ~ 250 Amp	90s ~ 3600s
200%	100 ~ 250 Amp	55s ~ 100s
300%	100 ~ 250 Amp	0.55s ~ 15s

**Ordering Information:**

Part Number	Ampere(A)	Voltage(VDC)	Body Color
1539 2300 200	30A	32 V	Orange
1539 2400 200	40A	32 V	Green
1539 2500 200	50A	32 V	Red
1539 2600 200	60A	32 V	Yellow
1539 2700 200	70A	32 V	Brown
1539 2800 200	80A	32 V	Clear
1539 3100 200	100A	32 V	Blue
1539 3125 200	125A	32 V	Pink
1539 3150 200	150A	32 V	Gary
1539 3200 200	200A	32 V	Violet

Tolerances : Unless Otherwise Specified		
Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material		GLORYTECH TECHNOLOGY CO., LTD.				
Drawn	Check	<b>Title:</b> <b>Mini Fuse Strip</b>		<b>A</b>	<b>GTQD-STP-1539</b>	<b>B</b>
Finish	Engr					
	Appd	Scale: 1:1		Dwg Size	Sht 1 of 1	Rev
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)						
Model File Name : Mini Fuse Strip with Housing						
Drawing File Name : GTQD-STP-1539						
Part Number : 1539 xxxx 200				Date:	2004/9/24	