



Electrical Characteristics:

% of Ampere Rating	Opening Time
100%	4 Hour Min.
250%	300sec. Max

- SPECIFICATIONS:
- Body Material : FR4
 - Metal Element : Brass/Copper
 - Finishing : Gold Plated or Nickel Plated

Part Number	Ampere Rating
1550 2350 *00	35 A
1550 2400 *00	40 A
1550 2500 *00	50 A
1550 2600 *00	65 A
1550 2700 *00	70 A
1550 2800 *00	80 A
1550 3100 *00	100 A
1550 3120 *00	120 A
1550 3125 *00	125 A
1550 3130 *00	130 A
1550 3150 *00	150 A
1550 3175 *00	175 A
1550 3200 *00	200 A
1550 3225 *00	225 A
1550 3250 *00	250 A
1550 3275 *00	275 A
1550 3300 *00	300 A
1550 3350 *00	350 A
1550 3400 *00	400 A

*=1 ; Gold Plated
 *=5 ; Nickel Plated

Tolerances : Unless Otherwise Specified

Dimension	Critical To Function	General
< 1	+/-0.02	+/-0.03
1 ~ 8	+/-0.1	+/-0.2
8 ~ 24.995	+/-0.15	+/-0.25
25 ~ 99.99	+/-0.2	+/-0.3
Angles	+/-1°	+/-5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material		Drawn		<p>GLORYTECH TECHNOLOGY CO., LTD.</p> <p>Title: Fuse Strip with Housing</p> <p>Unless Otherwise Specified Dimensions are mm (inch)</p> <p>Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)</p> <p>Scale: Dwg Size</p>	
Finish		Check			
Appd		Appd			
<p>Model File Name : Fuse Strip with Housing</p> <p>Drawing File Name : GTQD-STP-1550</p> <p>Part Number : 1550 xxxx *00</p>				<p>Date: 2004/9/24</p>	
		A4		GTQD-STP-1550	
		Dwg Size		Sht 1 of 1	
				Rev	