



Electrical Characteristics:

% of Rating	Opening Time
100 %	Carry
125 %	> 100 hr
300 %	100 ms ~ 10 s
600 %	20 ms ~ 1 s
1000 %	10 ~ 300 ms

Voltage(VDC) : 32V

Part no.	Rating	Material	T1(mm)	D(mm)
1565 2300 305	30A	Zinc	0.8	5.5
1565 2400 305	40A			
1565 2500 305	50A			
1565 2600 305	60A			
1565 2700 305	70A			
1565 2800 305	80A			
1565 3100 305	100A			
1565 3110 305	110A			
1565 3125 305	125A			
1565 3150 305	150A			
1565 3175 305	175A	Copper	0.6	6
1565 3200 306	200A			
1565 3225 306	225A			
1565 3250 306	250A			
1565 3300 306	300A			
1565 3300 306	300A	0.8		

Tolerances : Unless Otherwise Specified

Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material	Drawn	GLORYTECH TECHNOLOGY CO., LTD.			
	Check				
Finish	Engr	Title: Fuse Strip	A4	GTQD-STP-1565	B
	Appd				
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)		Scale: 2:1	Dwg Size	Sht 1 of 1	Rev
Model File Name : Fuse Strip					
Drawing File Name : GTQD-STP-1565					
Part Number : 1565 xxxx 30x			Date:	2011/8/24	